



# BETA 2 25-60/130 BR

**Circulator pumps with bronze body**



Energy-saving, electronic circulator pumps meeting the requirements for energy class A pumps, with a bronze body.

The pumps are equipped with an electronic processor that automatically controls the operation of the pumps, which, combined with a frequency converter, allows for significant savings in electricity consumption. The energy flow coefficient of BETA series pumps is  $EEL \leq 0,23$ . The pumps are equipped with an electronic display showing the current energy consumption

Model	Mode	Head (m)	Flow (l/min)	Motor power (W)	Power supply (V)	Connectors (inch)	Mounting length (mm)	Weight (kg)
BETA 25-60/130 BR	11	6	55	45	230	1½ / 1	130	2,8

# OHI 15-60/130 BR | OHI 25-60/130 BR

## Circulator pumps for domestic hot water.

Glandless, 3-speed circulator pumps designed to circulate hot utility water in larger installations. In installations, the pump is usually installed before the boiler or hot water tank. The pumps are certified by the National Institute of Hygiene.



National Institute of Public Health NIH  
- National Research Institute  
Hygienic Certificate



OHI 15-60/130 BR



OHI 25-60/130 BR

Model	Gear	Head (m)	Flow (l/min)	Motor power (W)	Power supply (V)	Connectors (inch)	Mounting length (mm)	Weight (kg)
OHI 15-60/130 BR	1 / 2 / 3	2,2 / 3,9 / 5,1	24 / 37 / 55	46 / 63 / 93	230	1 / ¾ (½)	130	2,6
OHI 25-60/130 BR	1 / 2 / 3	2,8 / 4,7 / 5,6	27 / 39 / 57	46 / 63 / 93	230	1½ / 1	130	2,8